

Methods

Nitrite, an intermediate in the nitrogen cycle, is formed during the decomposition of organic matter but readily oxidizes to form nitrate. These processes occur in wastewater treatment plants, water distribution systems, and natural waters. Nitrites are useful as corrosion inhibitors, preservatives, pigments, and in manufacturing many organic preservative chemicals. A Maximum Contaminant Level of 1 mg/L has been established by the USEPA for nitrite-nitrogen in drinking water.

Azo Dye Formation Method

References: APHA Standard Methods, 23rd ed., Method 4500-NO₂⁻ B-2000. USEPA Methods for Chemical Analysis of Water and Wastes, Method 354.1 (1983).

Nitrite diazotizes with a primary aromatic amine in an acidic solution to produce a highly colored azo dye. The intensity of the color is directly proportional to the concentration of nitrite in the sample. Nitrate will **not** interfere. Results are expressed as ppm (mg/L) NO₂-N.

The Ceric Sulfate Titrimetric Method

Reference: Developed by CHEMetrics.

Ceric sulfate is the titrant and ferroin is the end point indicator. The method is free from glycol interference in samples that contain up to 75% glycol, making it particularly applicable to systems that contain nitrite corrosion inhibitors. Results are expressed as ppm (mg/L) NaNO₂.

Visual Kits

Range: 0-2.5 ppm as N
MDL: 0.2 ppm / Method: Azo Dye Formation

	Cat#
CHEMets Kit	K-7004
CHEMets Refill, 30 ampoules, Shelf life 12 months	R-7002
Comparator, Shelf life 12 months 0, 0.2, 0.4, 0.6, 0.8, 1.0, 1.5, 2.0, 2.5 ppm	C-7004
Kit comes in a plastic case and contains everything needed to perform 30 tests: Refill, Comparator, 25 mL sample cup and instructions.	

Range: 0-80 ppm as N
MDL: 4 ppm / Method: Azo Dye Formation

	Cat#
VACUettes Kit	K-7004D
VACUettes Refill, 30 ampoules, Shelf life 12 months	R-7002D
Comparator, Shelf life 12 months 0, 10, 15, 20, 30, 45, 55, 65, 80 ppm	C-7004D
Kit comes in a plastic case and contains everything needed to perform 30 tests (except distilled water): Refill, Comparator, dilutor snapper cup, micro test tube and instructions.	

Range: 0-170 ppm as N
MDL: 10 ppm / Method: Azo Dye Formation

	Cat#
VACUettes Kit	K-7004A
VACUettes Refill, 30 ampoules, Shelf life 12 months	R-7002A
Comparator, Shelf life 12 months 0, 20, 30, 40, 60, 80, 110, 140, 170 ppm	C-7004A
Kit comes in a plastic case and contains everything needed to perform 30 tests (except distilled water): Refill, Comparator, dilutor snapper cup, micro test tube and instructions.	

Range: 0-300 ppm as N
MDL: 20 ppm / Method: Azo Dye Formation

	Cat#
VACUettes Kit	K-7004B
VACUettes Refill, 30 ampoules, Shelf life 12 months	R-7002B
Comparator, Shelf life 12 months 0, 40, 60, 80, 120, 180, 220, 260, 300 ppm	C-7004B
Kit comes in a plastic case and contains everything needed to perform 30 tests (except distilled water): Refill, Comparator, dilutor snapper cup, micro test tube and instructions.	

 Instrumental Kit

Range: 0-3000 ppm as N
MDL: 200 ppm / Method: Azo Dye Formation

VACUettes Kit	Cat# K-7004C
VACUettes Refill, 30 ampoules, Shelf life 12 months	R-7002C
Comparator, Shelf life 12 months 0, 400, 600, 800, 1100, 1500, 1900, 2400, 3000 ppm	C-7004C

Kit comes in a plastic case and contains everything needed to perform 30 tests (except distilled water): Refill, Comparator, dilutor snapper cup, micro test tube and instructions.

Range: 250-2500 ppm as NaNO₂
MDL: 250 ppm / Method: Ceric Sulfate Titrant with Ferroin Indicator

Titrets Kit	Cat# K-7025
--------------------	-----------------------

Increments:
250, 275, 300, 325, 350, 375, 400, 450, 500, 625, 750, 875, 1000, 1250, 1750, 2500 ppm

Kit comes in a cardboard box and contains everything needed to perform 30 tests: thirty ampoules with valve assemblies, titrettor, 25 mL sample cup and instructions.

Range: 500-5000 ppm as NaNO₂
MDL: 500 ppm / Method: Ceric Sulfate Titrant with Ferroin Indicator

Titrets Kit	Cat# K-7050
--------------------	-----------------------

Increments:
500, 550, 600, 650, 700, 750, 800, 900, 1000, 1250, 1500, 1750, 2000, 2500, 3500, 5000 ppm

Kit comes in a cardboard box and contains everything needed to perform 30 tests: thirty ampoules with valve assemblies, titrettor, 25 mL sample cup and instructions.

Multi-Analyte Photometers
V-2000 / V-3000
(See page 14 for instrumental features)

Range: 0-1.00 ppm as N
Method: Azo Dye Formation

Vacu-vials Kit , Shelf life 12 months	Cat# K-7003
--	-----------------------

Kit comes in a cardboard box and contains everything needed to perform 30 tests: thirty ampoules, 25 mL sample cup, ampoule blank and instructions.

Vacu-vials Kits require the use of a CHEMetrics Direct-Readout Photometer (photometers sold separately) or a spectrophotometer capable of accepting a 13 mm diameter round cell. See page 14 for details.

Components and Accessories	
Description	Cat#
Sample Cup Pack, 25 mL (6 ea)	A-0013
Micro Test Tube Pack (10 ea)	A-0015
Dilutor Snapper Cup Pack (6 ea)	A-0018
Ampoule Blank Pack (5 ea)	A-0023
* Sample Zeroing Accessory Pack	A-0025
Titrettor Pack (1 ea)	A-0053

* For use when testing colored or turbid samples. See page 13 for details.

Instructions and SDSs are posted on our website.

If no shelf life is listed for a product, then the shelf life is at least 1 year.

