

Safety Data Sheet

Version number: 12.1 SDS# R7501

SECTION 1: Identification

1.1 Product identifier

Trade name

Other means of identification

R-7501, R-7511, R-7518, R-7540, R-7540V, K-7553 Ampoules

Dissolved Oxygen CHEMets® & ULR CHEMets® Refills and Vacu-vials® Ampoules

1.2 Relevant identified uses of the substance or mixture and uses advised against

Component of water analysis test kits:

K-7501, K-7511, K-7518, K-7540, K-7553, K-7599, K-7599V

1.3 Details of the supplier of the safety data sheet

CHEMetrics, LLC. 4295 Catlett Road Midland VA 22728 United States

Telephone: 1-540-788-9026 Telefax: 1-540-788-4856 e-mail: technical@chemetrics.com Website: www.chemetrics.com

1.4 Emergency telephone number

Emergency information service

ChemTel Inc.: 1-800-255-3924, +01-813-248-0585

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Category	Hazard class and cat- egory	Hazard state- ment
3.10	acute toxicity (oral)	4	Acute Tox. 4	H302
3.1I	acute toxicity (inhal.)	5	Acute Tox. 5	H333
3.2	skin corrosion/irritation	1	Skin Corr. 1	H314
3.3	serious eye damage/eye irritation	1	Eye Dam. 1	H318
3.8	specific target organ toxicity - single exposure	2	STOT SE 2	H371

For full text of abbreviations: see SECTION 16.

R-7501, R-7511, R-7518, R-7540, R-7540V, K-7553 Ampoules

2023-03-24

2.2 Label elements

Labeling

- Signal word danger
- Pictograms

GHS05, GHS07, GHS08



- Hazard statements	
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H333	May be harmful if inhaled.
H371	May cause damage to organs.

- Precautionary stat	ements
P260	Do not breathe dusts or mists.
P264+P265	Wash hands thoroughly after handling. Do not touch eyes.
P270	Do not eat, drink or smoke when using this product.
P280	Wear eye protection/face protection.
P301+P317	IF SWALLOWED: Get medical help.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P302+P361+P354	IF ON SKIN: Take off immediately all contaminated clothing. Immediately rinse with water for several minutes.
P304+P317	IF INHALED: Get medical help.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P354+P338	IF IN EYES: Immediately rinse with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P311	IF exposed or concerned: Call a POISON CENTER/doctor.
P316	Get emergency medical help immediately.
P321	Specific treatment (see on this label).
P363	Wash contaminated clothing before reuse.
P405	Store locked up.
P501	Dispose of contents/container to industrial combustion plant.

2.3 Other hazards

Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of $\ge 0,1\%$.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
deionized water	CAS No 7732-18-5	≥67		
diethylene glycol	CAS No 111-46-6	27 - 31	Acute Tox. 4 / H302 Acute Tox. 4 / H332	(!)
methanol	CAS No 67-56-1	3-4	Flam. Liq. 2 / H225 Acute Tox. 3 / H301 Acute Tox. 3 / H311 Acute Tox. 3 / H331 STOT SE 1 / H370	
ТНАМ	CAS No 77-86-1	0.25		
potassium hydroxide	CAS No 1310-58-3	0.09	Acute Tox. 4 / H302 Skin Corr. 1A / H314 Eye Dam. 1 / H318	
proprietary_06		0.06	Skin Irrit. 2 / H315 Eye Irrit. 2A / H319 STOT SE 3 / H335	()
proprietary_01		0.01 - 0.02	Water-react. 1 / H260 Acute Tox. 3 / H301 Acute Tox. 5 / H313 Acute Tox. 4 / H332 Skin Corr. 1C / H314 Eye Dam. 1 / H318 Repr. 1B / H360F Aquatic Acute 3 / H402 Aquatic Chronic 3 / H412 CDust001	
proprietary_05		0.001	Acute Tox. 4 / H302 Acute Tox. 5 / H313 Aquatic Acute 1 / H400 Aquatic Chronic 1 / H410	

For full text of abbreviations: see SECTION 16.

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, Alcohol resistant foam, BC-powder, Carbon dioxide (CO2)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Nitrogen oxides (NOx), Carbon monoxide (CO), Carbon dioxide (CO2)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 **Precautions for safe handling**

Recommendations

Wear impact- and splash-resistant eyewear. Break the ampoule tip only when it is completely immersed in sample. Breaking the tip in air may cause the glass ampoule to shatter.

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

- Handling of incompatible substances or mixtures

Do not mix with acids.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

7.3 Other information

For optimum analytical performance, store in the dark and at room temperature.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occup	Occupational exposure limit values (Workplace Exposure Limits)										
Coun- try	Name of agent	CAS No	Identi- fier	TWA [ppm]	TWA [mg/m³]	STEL [ppm]	STEL [mg/m³]		Ceiling-C [mg/m³]		Source
US	potassium hydrox- ide	1310-58-3	REL						2		NIOSH REL
US	potassium hydrox- ide	1310-58-3	TLV®						2		ACGIH® 2023
US	potassium hydrox- ide (caustic potash)	1310-58-3	PEL (CA)						2		Cal/ OSHA PEL
US	methanol	67-56-1	TLV®	200		250				Н	ACGIH® 2023
US	methyl alcohol	67-56-1	REL	200 (10 h)	260 (10 h)	250	325				NIOSH REL
US	methyl alcohol	67-56-1	PEL	200	260						29 CFR 1910.100 0
US	methyl alcohol (methanol)	67-56-1	PEL (CA)	200	260	250	325	1,000			Cal/ OSHA PEL

Notation	
Ceiling-C	ceiling value is a limit value above which exposure should not occur
Н	absorbed through the skin
STEL	short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
TWA	time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time- weighted average (unless otherwise specified

Biological limit values							
Country	Name of agent	Parameter	Notation	Identifier	Value	Source	
US	methanol	methanol		BEI®	15 mg/l	ACGIH® 2023	

Relevant DNELs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
diethylene glycol	111-46-6	DNEL	44 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic ef- fects
diethylene glycol	111-46-6	DNEL	60 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
diethylene glycol	111-46-6	DNEL	43 mg/kg bw/ day	human, dermal	worker (industry)	chronic - systemic ef- fects
methanol	67-56-1	DNEL	130 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic ef- fects
methanol	67-56-1	DNEL	130 mg/m ³	human, inhalatory	worker (industry)	acute - systemic ef- fects
methanol	67-56-1	DNEL	130 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
methanol	67-56-1	DNEL	130 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
methanol	67-56-1	DNEL	20 mg/kg bw/ day	human, dermal	worker (industry)	chronic - systemic ef- fects
methanol	67-56-1	DNEL	20 mg/kg bw/ day	human, dermal	worker (industry)	acute - systemic ef- fects
THAM	77-86-1	DNEL	117.5 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic ef- fects
THAM	77-86-1	DNEL	166.7 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic ef- fects
potassium hydroxide	1310-58-3	DNEL	1 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
proprietary_05		DNEL	1 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic ef- fects
proprietary_05		DNEL	1 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
proprietary_05		DNEL	137 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic ef- fects

Relevant PNECs of	component	s of the m	Relevant PNECs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time			
diethylene glycol	111-46-6	PNEC	10 ^{mg} / _l	aquatic organisms	freshwater	short-term (single ir stance)			
diethylene glycol	111-46-6	PNEC	1 ^{mg} / _l	aquatic organisms	marine water	short-term (single ir stance)			
diethylene glycol	111-46-6	PNEC	199.5 ^{mg} / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single in stance)			
diethylene glycol	111-46-6	PNEC	20.9 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single i stance)			
diethylene glycol	111-46-6	PNEC	2.09 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single i stance)			
diethylene glycol	111-46-6	PNEC	1.53 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single i stance)			
methanol	67-56-1	PNEC	20.8 ^{mg} / _l	aquatic organisms	freshwater	short-term (single i stance)			
methanol	67-56-1	PNEC	2.08 ^{mg} / _l	aquatic organisms	marine water	short-term (single i stance)			
methanol	67-56-1	PNEC	100 ^{mg} / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single i stance)			
methanol	67-56-1	PNEC	77 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single i stance)			
methanol	67-56-1	PNEC	7.7 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single i stance)			
methanol	67-56-1	PNEC	100 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single i stance)			
THAM	77-86-1	PNEC	300 ^{mg} / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single i stance)			
proprietary_01		PNEC	1.75 ^{mg} / _l	aquatic organisms	freshwater	short-term (single i stance)			
proprietary_01		PNEC	1.75 ^{mg} / _l	aquatic organisms	marine water	short-term (single i stance)			
proprietary_01		PNEC	54.77 ^{mg} / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single i stance)			
proprietary_01		PNEC	2.55 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single i stance)			
proprietary_01		PNEC	0.255 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single i stance)			
proprietary_01		PNEC	4.8 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single i stance)			
proprietary_05		PNEC	7.8 ^{µg} / _l	aquatic organisms	freshwater	short-term (single i stance)			
proprietary_05		PNEC	5.2 ^{µg} / _l	aquatic organisms	marine water	short-term (single i stance)			
proprietary_05		PNEC	230 ^{µg} / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single i stance)			

Relevant PNECs of components of the mixture

	•					
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
proprietary_05		PNEC	87 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single in- stance)
proprietary_05		PNEC	676 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single in- stance)
proprietary_05		PNEC	65 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single in- stance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Product description CHEMets Refills: Sealed glass ampoules, 7 mm OD, for visual colorimetric water analysis. Each CHEMet[™] ampoule contains approximately 0.2 - 0.5 mL of liquid reagent sealed under vacuum. Refills contain 30 ampoules, test kits contain 1 refill.

ULR CHEMets Refills: Sealed glass ampoules, 250 mm length, for visual colorimetric water analysis. Each ULR CHEMet[™] ampoule contains approximately 1 mL of liquid reagent sealed under vacuum. Refills contain 30 ampoules, test kits contain 1 refill

Vacu-vials Ampoules: Sealed glass ampoules, 13 mm OD, for instrumental colorimetric water analysis. Each Vacu-vial™ ampoule contains approximately 0.8 - 2 mL of liquid reagent sealed under vacuum. Test kits contain 30 ampoules.

Appearance

Physical state	liquid
Color	Colorless to greenish yellow
Particle	not relevant (liquid)
Odor	odorless

Other safety parameters

pH (value)	11.5 (base)
Melting point/freezing point	-5 °C
Initial boiling point and boiling range	150 °C at 1,013 hPa
Flash point	not determined
Evaporation rate	Not determined
Flammability (solid, gas)	not relevant, (fluid)
Vapor pressure	169.3 hPa at 25 °C
Density	not determined
Vapor density	this information is not available
Relative density	1.03 (water = 1)

Solubility(ies)

- Water solubility	miscible in any proportion
--------------------	----------------------------

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	372 °C (auto-ignition temperature (liquids and gases))
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

Oxidizers

Release of flammable materials with:

Light metals (due to the release of hydrogen in an acid/alkaline medium)

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Harmful if swallowed.

GHS of the United Nations, annex 4: May be harmful if inhaled.

- Acute toxicity estimate (ATE)

Oral 1,087 ^{mg}/_{kg}

Acute toxicity estimate (ATE) of compone	nts of the mixtu	re	
Name of substance	CAS No	Exposure route	ATE
diethylene glycol	111-46-6	oral	500 ^{mg} / _{kg}
diethylene glycol	111-46-6	inhalation: vapor	11 ^{mg} /ı/4h
diethylene glycol	111-46-6	inhalation: dust/mist	>4.6 ^{mg} / _l /4h
methanol	67-56-1	oral	100 ^{mg} / _{kg}
methanol	67-56-1	dermal	300 ^{mg} / _{kg}

Acute toxicity estimate (ATE) of components of the mixture

		_	
Name of substance	CAS No	Exposure route	ATE
methanol	67-56-1	inhalation: vapor	3 ^{mg} / _l /4h
potassium hydroxide	1310-58-3	oral	333 ^{mg} / _{kg}
proprietary_01		oral	56.57 ^{mg} / _{kg}
proprietary_01		inhalation: dust/mist	>1.295 ^{mg} / _l /4h
proprietary_05		oral	482 ^{mg} / _{kg}

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

May cause damage to organs.

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance in a concentration of $\geq 0,1\%$.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of $\ge 0,1\%$.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

please consider the relevant national or regional provisions

SECT	ION 14: Transport information	
14.1	UN number	not subject to transport regulations
14.2	UN proper shipping name	
14.3	Transport hazard class(es)	none
14.4	Packing group	not assigned
14.5	Environmental hazards	non-environmentally hazardous acc. to the danger- ous goods regulations

14.6 Other relevant information

Shipping container markings and labels, received from CHEMetrics, may vary from the above information. Products that are regulated for transport will be packaged by CHEMetrics as Dangerous Goods in Excepted Quantities according to IATA, US DOT, and IMDG regulations. CHEMetrics may also elect to ship certain products as UN 3316 Chemical Kit, Hazard Class 9, Packing Group II or III. In case of reshipment, it is the responsibility of the shipper to determine appropriate labels and markings in accordance with applicable transportation regulations.

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

Not subject to transport regulations.

International Maritime Dangerous Goods Code (IMDG) - Additional information

Not subject to IMDG.

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Not subject to ICAO-IATA.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

- Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Tox	ic Chemical List	ings	
Name of substance	CAS No	Remarks	Effective date
methanol	67-56-1		1986-12-31

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	Remarks	Statutory code	Final RQ pounds (Kg)
potassium hydroxide		1	1000 (454)
methanol		3 4	5000 (2270)

Legend

1 "1" indicates that the statutory source is section 311(b)(2) of the Clean Water Act

3 "3" indicates that the source is section 112 of the Clean Air Act

4 "4" indicates that the source is section 3001 of the Resource Conservation and Recovery Act (RCRA)

Clean Air Act

none of the ingredients are listed

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals			
Name acc. to inventory	CAS No	Remarks	Type of the toxicity
methanol	67-56-1		developmental

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	/	none
Health	3	major injury likely unless prompt action is taken and medical treatment is given
Flammability	1	material that must be preheated before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	1	material that must be preheated before ignition can occur
Health	3	material that, under emergency conditions, can cause serious or permanent injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
US	TSCA	not all ingredients are listed
AU	AIIC	not all ingredients are listed
CA	DSL	not all ingredients are listed
CN	IECSC	not all ingredients are listed
EU	ECSI	not all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
KR	KECI	not all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	not all ingredients are listed
PH	PICCS	not all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	not all ingredients are listed

Legend

Legena	
AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
KECI	Korea Existing Chemicals Inventory

Legend	
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture. Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H225	Highly flammable liquid and vapor.
H260	In contact with water releases flammable gases, which may ignite spontaneously.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H313	May be harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H333	May be harmful if inhaled.
H335	May cause respiratory irritation.
H360F	May damage fertility.
H370	Causes damage to organs.
H371	May cause damage to organs.
H400	Very toxic to aquatic life.
H402	Harmful to aquatic life.

Code	Text
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.