Nitrite HR CHEMets® Kit

K-7020B/R-7002/A-0171: 0 - 250 ppm

Test Procedure

- Place a pipette tip firmly onto the end of the MiniPet^{®4} (fig. 1).
 NOTE: Use a fresh pipette tip for each test.
- 2. Depress the plunger on the minipet.
- Immerse the tip in the sample to be tested and release the plunger. A portion of the sample will be drawn into the tip (fig. 2).
 NOTE: Do not touch the side or bottom of the sample container with the tip during sampling.
- 4. Hold the minipet over the sample cup, and depress the plunger to dispense sample (fig. 3).
- 5. Dilute the contents of the sample cup to the **20 ml mark with distilled water** (fig. 4).
- 6. Place the CHEMet ampoule, tip first, into the sample cup. Snap the tip. The ampoule will fill leaving a bubble for mixing (fig. 5).
- 7. To mix the ampoule, invert it several times, allowing the bubble to travel from end to end.











- 8. Dry the ampoule. Obtain a test result **10 minutes** after snapping the tip.
- Use the 0 250 ppm concentration scale of the comparator label. Obtain a test result by placing the ampoule between the color standards until the best color match is found (fig. 6).



Figure 6

NOTE: To convert to ppm nitrite (NO₂), multiply test result by 3.3.

Test Method

The Nitrite CHEMets^{®1} test kit employs the azo dye formation method.^{2,3} In an acidic solution, nitrite diazotizes with a primary aromatic amine and then couples with another organic molecule to produce a highly colored azo dye. The resulting pink-orange color is proportional to the nitrite concentration in the sample.

- 1. CHEMets is a registered trademark of AquaPhoenix Scientific, LLC U.S. Patent No. 3,634,038
- 2. APHA Standard Methods, 23rd ed., Method 4500-NO2- B -2000
- 3. EPA Methods for Chemical Analysis of Water and Wastes, Method 354.1 (1983).
- 4. Minipet is a registered trademark of Tricontinent Scientific, Inc.

Safety Information

Read SDS before performing this test procedure. Wear safety glasses and protective gloves.

